

Model # MU3000RM3U / MU3000RM2U

Smart Online double conversion Technology, 1-Ph, 200-240V, 50/60Hz, 3KVA/2.7KW with Dual bypass modes

Product Description:

Magnizon MU3000RM3U/2U 3000VA /2700 watt Smart online, double-conversion UPS system offers complete power protection for critical applications. True online, double-conversion technology supports the critical loads with zero transfer time(0mSec), suitable for advanced networking applications. Fault-tolerant Static-bypass prevents unexpected service interruptions during UPS overload or internal fault conditions. With built-in manual bypass switch enables hot-swappable replacement of entire UPS power module with zero down time to connected equipment. Elegant LCD display with vast scope of monitoring and setting up of various paraments make UPS tailored for each specific application.



Front View



Rear view



Key Features:

- ❖ Magnizon MU3000RM3U/2U 2KVA/1.8KW smart on-line, double-conversion UPS system in 3U total rack/tower configuration
- ❖ Maintains full-time pure sine wave output within 2% of selectable 220/230/240V nominal during brownouts as low 110V and over voltages as high as 300V
- ❖ Fault tolerant electronic bypass maintains utility output during a variety of UPS fault conditions
- ❖ Online double conversion technology With advanced DSP control
- ❖ Wide input voltage range(110~300VAC) can adapt to different power grid environment
- ❖ DC start (cold start) function
- ❖ Input PFC filters
- ❖ Built-in static bypass
- ❖ Input power factor above 0.98 and Output power factor of 0.9
- ❖ Built in 8nos of IEC C13 outlets
- ❖ Strong over load capacity
- ❖ Supporting rack/tower structure, high power density saving space
- ❖ Built-in protections: Over voltage, Over load, Over current, Battery overcharge, Battery deep discharge protection, battery low voltage protection
- ❖ LCD display and LED indicator show detailed UPS status and parameters
- ❖ Friendly man-machine interface, Simple setting Output Voltage, Frequency parameter and Bypass function on the display
- ❖ Lightning, surge, short -circuit, network/fax/modem surge protection
- ❖ Smart RS232 communication with monitoring software
- ❖ Full-time active power conditioning provides clean, continuous dual-conversion AC output free of voltage fluctuations, power interruptions and line noise
- ❖ Double-conversion operation converts raw input from AC to DC, then resynthesizes output power back to perfect sine wave AC with enhanced protection from harmonic distortion, fast electrical impulses and other hard-to-solve power problems not addressed by other UPS types
- ❖ Supports 50/60Hz operation for worldwide frequency compatibility
- ❖ Expandable runtime is supported with optional BP192V9RM3U or any 192V battery DC bus external battery packs
- ❖ Intelligent battery management system with temperature-compensated charging with advanced 4-stage battery charging algorithm extends battery life
- ❖ Battery independent restart ensures automatic UPS power-up without user interaction after lengthy power outages, even when batteries are expired and require replacement
- ❖ Rack mount and tower mount kits included for both Battery pack and UPS module
- ❖ Adjustable telescopic rail kits suits any depth of the rack
- ❖ LED / LCD display panel rotates for viewing in rackmount or tower configurations
- ❖ Network-grade AC surge and noise suppression
- ❖ External battery packs are field replaceable and hot swappable

Model # MU3000RM3U / MU3000RM2U

Package includes:

- ❖ MU3000RM3U , 3KVA 3U power module
- ❖ Four post compatible, telescopic adjustable rack rail kit -2 sets
- ❖ Tower stands for upright tower configuration
- ❖ RS232 cabling and CD
- ❖ User manual

Specifications:

Model No	MU3000RM3U	MU3000RM2U
Capacity	3000VA/2700W	
INPUT DATA		
Rated input current (Maximum Load)	14.6Amp	
Nominal Input Voltage(s) Supported	220V AC; 230V AC; 240V AC	
UPS Input Connection Type	IEC C14 inlet	
UPS Input Connection Description	230/220/240V (L,N,PE) input wiring, 50/60Hz	
Recommended Electrical Service	16Amp	
Input Phase	Single-Phase, 3W system (L,N,PE)	
OUTPUT DATA		
Output Volt Amp Capacity (VA)	3000	
Output kVA Capacity (kVA)	3KVA	
Output Watt Capacity (Watts)	2700	
Output kW Capacity (kW)	2.7KW	
Output Capacity Details	Supports up to 110% load continuously in double conversion mode, 111 to 125% for 12minute, 126% to 150% for 55 seconds; Loads over 150% trigger immediate bypass mode operation to support loads directly from mains power; Double conversion mode is automatically restored as load levels are reduced to 95% or less	
Power Factor	0.9	
Crest Factor	3:01	
Nominal Output Voltage(s) Supported	220V; 230V; 240V	
Nominal Voltage Details	Voltage selection via front panel LCD interface	
Frequency Compatibility	50 / 60 Hz; Supports 50 to 60 Hz and 60 to 50 Hz conversion	
Output Voltage Regulation (Line Mode)	+/- 2%	
Output Voltage Regulation (Economy Line Mode)	+/- 10%	
Output Voltage Regulation (Battery Mode)	+/- 2%	
Output Receptacle Details	8no of IEC C13	
Output AC Waveform (AC Mode)	Pure Sine wave	
Output AC Waveform (Battery Mode)	Pure Sine wave	

Model # MU3000RM3U / MU3000RM2U

VOLTAGE REGULATIONS & SURGE DATA		
Voltage Regulation Description	2% output voltage regulation in standard online, double-conversion mode	
Overvoltage Correction	Corrects over voltages up to 300V	
Undervoltage Correction	Corrects under voltages as low as 110V	
UPS AC Suppression Joule Rating	1410	
UPS AC Suppression Response Time	Instantaneous	
EMI / RFI AC Noise Suppression	Yes	
BATTERY DETAILS		
Full Load Runtime (min.)	5min. (2700W)	External battery only
Half Load Runtime (min.)	11.8 min. (1350W)	External battery only
Expandable Battery Runtime	Supports extended runtime with optional external battery packs	
External Battery Pack Compatibility	BP72V18RT3U, BP72V27RT3U	
DC System Voltage (VDC)	72V DC	
Battery Recharge Rate (Included Batteries)	Less than 5 hours from 10% to 90% (typical, full load discharge)	Depends on battery models and numbers
Battery Replacement Description	Hot-swappable, user replaceable external battery packs	
Expandable Runtime	Yes, with additional battery packs	
Transfer Time	0mSec in online, double-conversion mode	
Low Voltage Transfer to Battery Power	110V	
High Voltage Transfer to Battery Power	300V	
USER INTERFACE AND CONTROLS		
Front Panel LCD Display	Selectable LCD display with scroll and selection buttons enables UPS control and detailed monitoring options; LED/LCD panel rotates for viewing in rack/tower formats	
Switches	2 Switches control off/on power status and alarm-cancel/self-test operation; 2 additional switches support set and execute scrolling LCD functions;	
Alarm Cancel Operation	Alarm cancel switch	
Audible Alarm	Unique audible alarms for all major UPS, environmental and power conditions (see manual)	
LED Indicators	LEDs indicate line power, online mode, economy/bypass mode, on-battery, charger and AC output status; LCD screen offers additional information and control options	
PHYSICAL DETAILS		
Installation Form Factors Supported with Included Accessories	4 post 19 inch rackmount	
Included Mounting Accessory Description	2 sets of adjustable 4 post rack rails included; 2-9USTAND tower kit included	
Primary Form Factor	Rackmount or tower mount	
UPS Power Module Dimensions (hwd, mm)	133x440x558	89x440x438
Rack Height	3U	2U
UPS Dimensions Details	Includes 3U UPS/power module	Includes 2U UPS/power module
Included Battery Pack Weight (kg)	26.8kgs + 3kgs for rail kits	9kgs + 3kgs for rail kits

Model # MU3000RM3U / MU3000RM2U

Shipping Dimensions (hwd / mm)	169 x 50.29 x 430	169 x 50.29 x 430
Shipping Weight (kg)	29.8kgs (with battery)	12Kgs
Cooling Method	Smart Fan with variable speed based on temperature	Smart Fan with variable speed based on temperature
UPS Housing Material	Steel	Steel
ENVIRONMENTAL		
Operating Temperature Range	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius	
Storage Temperature Range	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius	
Relative Humidity	0 to 95%, non-condensing	
AC Mode BTU / Hr. (Full Load)	930	
AC Economy Mode BTU / Hr. (Full Load)	415	
Battery Mode BTU / Hr. (Full Load)	1230	
AC Mode Efficiency Rating (100% Load)	94%	
AC Economy Mode Efficiency Rating-full Load	98%	
Operating Elevation (ft.)	0-3000m (0 to 10,000 ft.)	
Audible Noise	40 dBA at front side 1 meter	
Operating Elevation (m)	0-3000 m	
COMMUNICATIONS		
Communications Interface	USB (HID enabled); DB9 Serial; EPO (emergency power off); Slot for SNMP/Web interface	
Network Management Cards	snmp-up1	
Software compatibility	Windows family all versions, Linex, Sun Network OS, IBM Aix, Compaq Tru64 SGI IRIX, FreeBSD, HP-UX and MAC	
UPS monitoring Software	Supplied along with UPS. Optional SNMP card with web based available on request	
Network Surge	RJ45 I/O ports available for network or FAX/Modem	
Communications Cable	USB & DB9 serial	
CERTIFICATIONS & WARRANTY		
UPS Certifications	CE, EN/IEC 62040-1:2008, EN/IEC 62040-2:2006, EN/IEC 61000-3-3:2013, EN/IEC 61000-3-2:2014	
UPS Quality standards	ISO9001:2015, ISO14001:2015, RoHs	
Product Warranty Period (Worldwide)	2-year limited warranty	

Copyright © 2012 MAGNIZON POWER SYSTEMS. All rights reserved. All trademarks are the sole property of their respective owners. MAGNIZON POWER SYSTEMS has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.